

RAZORBACK

12



A rigorous process – for a resilient canvas

You already know that Razorback 12 promises maximum durability and weather resistance – season after season. And that’s not by accident.

It’s all thanks to the meticulous Razorback manufacturing process. Tried and tested.

KEY FEATURES

UV resistant

Mildew resistant

Highly water resistant

No heavy metals

No mercury

Dimensionally stable

Our process begins with a tightly woven loomstate base fabric, using a blended 2 ply polyester/cotton ring spun yarns in both directions. From there, we:

1. Scour the fabric to remove oils, lubricants and impurities
2. Immerse it in a pad bath filled with colour, mildew and water-resistant properties
3. Pass it through nip rollers to squeeze the chemicals into the fabric
4. Dry it by passing through high temperature steam filled cylinders allowing the fabric to relax naturally

We then repeat the process to reinforce our treatment.

SPECIFICATIONS

WIDTH	204cm
FINISHED WEIGHT (AS2001.13)	490gsm on average
SHRINKAGE	Warp – 3% Weft – 1%
HYDROSTATIC HEAD (AS2001.2.17)	700mm minimum
CONE TEST (AS2001.2.18)	PASS
TEAR STRENGTH (AS2001.2.10)	Warp – 70N Weft – 45N
TENSILE STRENGTH (AS2001.2.3)	Warp – 2000N/50mm Weft – 1350N/50mm
RUB FASTNESS (AS2001.4.3)	Dry - 5 Wet - 4.5

The Razorback 5-year customer guarantee

At Paskal, we do more than simply *promise* integrity. We back it up – with fair and simple guarantees.



At Paskal, we guarantee our outdoor canvas fabrics can withstand outdoor conditions for at least 5 years – except in the case of severe and unusual abrasions or mechanical stresses.

We will replace or restore fabric at our discretion if it has failed to provide satisfactory service within the 5-year guarantee period.

This guarantee will **not** apply if:

- Care instructions have not been followed
- The canvas presents typical woven characteristics (such as yarn slubs and knots)
- The canvas has endured unreasonable treatment or extraordinary weather conditions
- The problem resulted from the work of a third party (such as finished product manufacturers or installers)

This guarantee only relates to the Razorback Canvas. It does not cover any costs or losses relating to dismantling, transport or re-erection.

All claims for replacement and restoration must be made by end-customers.

How to care for your canvas

Follow these care instructions to keep your canvas robust and resilient for years to come.

- Wet the canvas thoroughly before use and allow it to dry. Repeat 2-3 times to ensure seams are sealed.
- Clean canvas regularly with a soft brush, inside and outside.
- Hose canvas occasionally with clear, cold water. Start at the lower edges and work upwards.
- Avoid soaps, detergents, cleaning fluids, insecticides, petrol, solvents, kerosene and other similar fluids.
- Ensure the canvas is dry before putting it away.
- Keep canvas clear of bird droppings, dirt, sand and vegetable matter.
- Brush mildew spots off canvas before they stain.
- Treat persistent mould or mildew growth with White King solution (following the solution's instructions).

Extensively cleaned canvas may require reproofing. We recommend **Paskal Proofcoat**.