



Size 20 Moulded **Premium** Zipper

by Paskal

Technical Data v21

Applications

Pk20 Zip provides strength necessary to withstand Mechanical forces common in large scale industrial fabric applications.

Materials

Teeth:

Delrin (Virgin material)
(colours other than Black have added UV resistant additives)

Tape: (100% texturized polyester yarns)

- Water repellent
- UV resistant treatments

Dimensions

Total Zip Width:73.0mmTape Width:33.0mmTeeth Width:19.0mmTeeth Thickness:7.8mmTape Thickness:0.59mmLength tolerance on made zips:1% or 12mm

(whichever is the smallest)

Strength Data

Lateral strength:

1500N (152kg)

Durability:

500 reciprocating cycles

Holding strength of open-end unit:

700N (71kg)

Standards

Passes or exceeds:

AS2332.2003 (Lateral Strength):

Exceeds Australian Standard of 490N (actual result 1500N)

Available Sliders

Plastic (Delrin):

• Single Pull Auto-Lock with Ring Puller

Product Features

- Exceptional high strength
- Smooth zip operation
- High UV resistance
- Lay flat tape
- Water-resistant tap

Head Office - Victoria

9A Lakewood Blvd, BRAESIDE VIC 3195 **P:** 03 9588 8800 **E:** paskal@paskal.com.au

Queensland

4 Aranda St,
SLACKS CREEK QLD 4127
P: 07 3440 7000
E: qld@paskal.com.au

Western Australia

1/17 Sphinx Way, BIBRA LAKE WA 6163 **P:** 08 9236 3400 **E:** wa@paskal.com.au

Tasmania

HOBART TAS 7000 **P:** 03 6295 2100 **E:** tas@paskal.com.au