

PASKAL

LEADING INNOVATION IN PERFORMANCE FABRICS + ACCESSORIES

SHOCKCORD TECHNICAL SPECIFICATIONS

ALSO KNOWN AS BUNGEE OR SHOCK CORD, ELASTIC CORD IS DESIGNED FOR STRENGTH AND FLEXIBILITY. IT IS COMMONLY USED TO TIE DOWN TENTS, SECURE OBJECTS IN THE TRAY OF A TRUCK, OR FASTEN TARPS.

CONSTRUCTED WITH A DURABLE, SOLUTION-DYED POLYESTER JACKET TO RESIST FADING, ROT, AND UV DAMAGE, AND REINFORCED WITH INNER RUBBER STRANDS, THE CORD OFFERS EXCELLENT ELASTICITY AND RELIABLE PERFORMANCE.

BUNJI LOOPS ARE ALSO PRODUCED USING SOLUTION-DYED YARN, ENSURING ENHANCED UV PROTECTION FOR LONGER-LASTING OUTDOOR USE.

PRODUCT	SHOCKCORD		
SPECIFICATION	DIAMETER	6MM	8.0MM
	YARN	SOLUTION DYED FILAMENT POLYESTER	
	CORE	NATURAL RUBBER	
	COLOUR	BLACK	BLACK
	WEIGHT	9.52 G/FOOT	15.59 G/FOOT
	ELONGATION	100% +/- 10%	100% +/- 10%
	ELONGATION AT BREAK %	158	146
	PICK PER INCH	32	24
	TENSILE	APPROX. 4.8 – 5.2KG	APPROX. 9.8 - 10.5KG
	MODULUS @ 25% (LBS)	5.89 LBS	12.10 LBS
	MODULUS @ 50% (LBS)	8.09 LBS	17.53 LBS
	MODULUS @ 75% (LBS)	10.89 LB	26.74 LBS
	MODULUS @ 100% (LBS)	14.55 LBS	49.56 LBS
	MODULUS @ BREAKING (LBS)	138.60 LBS	251.32 LBS

VICTORIA – Head Office

P 03 9588 8800
E paskal@paskal.com.au

9A Lakewood Boulevard,
Braeside, VIC 3195

NEW SOUTH WALES

P 02 9607 1801
E nsw@paskal.com.au

QUEENSLAND

P 07 3440 7000
E qld@paskal.com.au

WESTERN AUSTRALIA

P 08 9236 3400
E wa@paskal.com.au

TASMANIA

P 03 6295 2100
E tas@paskal.com.au



PASKAL.COM.AU